



## P046040MIS

<b>CAPACITY, DIMENSIONS, WEIGHT</b>	///
Capacity trays	4 TRAYS 600x400 - GN 1/1
Distance between trays (mm)	80
Type of rack holder	GRID
Unit size with handle WxDxH (mm)	800 x 795 x 577
Unit size without handle WxDxH (mm)	800 x 733 x 577
Chamber size WxDxH (mm)	694 x 455 x 345
Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	850 x 850 x 740
Unit weight (kg)	55
Unit weight with packaging (kg)	67
<b>ELECTRICAL DATA</b>	///
Number of engines	2
Frequency (Hz)	50/60
Power (kW)	7,4
Voltage A	400V 3N~
B	400V 2N~
C	230V ~
D	230V 3~
Current (A) A	12,2
B	22,2
C	32,2
D	21,1

Power cord/power plug	A
	B
	C
	D
<b>WATER CONNECTION REQUIREMENTS</b>	///
Water inlet	YES
Water drain	-
Minimum water quality standards	5° f
<b>FUNCTIONAL CHARACTERISTICS</b>	///
Supply	ELECTRIC
Certification	CB
Control panel	MECHANICAL
Multilingual screen	-
Cooking type	CONVECTION
Bidirectional motors	YES
Two speed regulation	-
Max cooking temperature (°C)	280
Cooking chamber material	AISI 430
Opening door	FROM TOP TO BOTTOM
Easy clean internal glass	-
<b>STANDARD EQUIPMENT</b>	///
Self clean system	-
Core probe	-
<b>VARIANTS AVAIABLES</b>	///
Certification	-
Unit size with handle WxDxH (mm)	800 x 781 x 577
Unit size without handle WxDxH (mm)	800 x 733 x 577
Frequency (Hz)	-
Power (kW)	-
Voltage	A -
	B -
	C -
	D -
Current (A)	A -
	B -
	C -
	D -
Power cord / power plug	A -

	B	-
	C	-
	D	-
Packaging		-
Packaging size WxDxH (mm)		-
<b>ACCESSORIES</b>		///
Self clean system		-
Stainless steel tray rack holder		-
Stainless steel grid rack holder		"5 TRAYS GN 1/1 67mm"
Oven stand		T8
		T8S
		T8SL
Wheels kit for stand		H8
Condensation hood		-
Water condensation hood		CA8008M0
Proofer		CA8008MH
		CA8088DH
		CA8016M0
Overlapping kit for 2 ovens		SK3
Blast chiller		ASP05
		-
		-
Overlapping kit for blast chillere + 1 ovens		-
Smoker		-
Core probe		WS10
Core probe for vacuum		WS11
Water softner cover		WS12
Water softner 6800L		WPA
Water softner 12000L		-
Water pressure adaptor		-
Manual shower kit		-
"Detergent 750ML (for Self clean system or Manual shower kit)"		-
"Detergent 6KG (only with self clean system)"		-
"Detergent 10KG (only with self clean system)"		-

## FEATURES

◆ Standard | ◇ Optional | - Not available

MANUAL COOKING			M
Convection cooking	30°C - 285°C	◆	
Mixed humidity and convection cooking	90°C - 230°C	◆	
Humidity		◆	
AUTOMATIC COOKING			
Program: possibility to memorize program		-	
V-EVOLUTION CONTROL WITH 6 SPEED PROGRAMS		-	
Cooking cycles for each program		-	
Automatic pre-heating setting		-	
AIR DISTRIBUTION IN THE COOKING CHAMBER			
V-BI.DIRETIONAL REVERSING FAN		◆	
V-POWERFULL ENGINE		◆	
Number of speed regulation		-	
OVERLAP SYSTEM			
V- OVERLAP CONNECTION with ovens		◇	
V- OVERLAP CONNECTION with WLBAKE's Proofing		◇	
V- OVERLAP CONNECTION with WLBAKE's Stand		◇	
OTHER FUNCTIONS			
Infinity time		◆	
Temperature parameter unit F° or C°		◆	
V - LIGHTS	Halogen	◆	
USB		-	
TECHNICAL DETAILS			
Internal glass easy clean system		◆	
Thermal insulation structure (energetic efficiency)		◆	
Humidity regulation	Manual	◆	